



金宏不銹鋼材有限公司

金城特殊金屬股份有限公司

工業配管用不銹鋼管 Stainless steel pipe

ASTM A312/A358/A778, ANSI/ASME B36.19M

稱呼外徑 outside diameter		thickness 厚度 外徑 mm	SCH 5S	SCH 10S	SCH 40S
N.B	NPS		mm	mm	mm
8	1/4"	13.72		1.65	2.24
10	3/8"	17.15		1.65	2.31
15	1/2"	21.34	1.65	2.11	2.77
20	3/4"	26.67	1.65	2.11	2.87
25	1"	33.40	1.65	2.77	3.38
32	1 1/4"	42.16	1.65	2.77	3.56
40	1 1/2"	48.26	1.65	2.77	3.68
50	2"	60.33	1.65	2.77	3.91
65	2 1/2"	73.03	2.11	3.05	5.16
80	3"	88.90	2.11	3.05	5.49
90	3 1/2"	101.60	2.11	3.05	5.74
100	4"	114.30	2.11	3.05	6.02
125	5"	141.30	2.77	3.40	6.55
150	6"	168.28	2.77	3.40	7.11
200	8"	219.08	2.77	3.76	8.18
250	10"	273.05	3.40	4.19	9.27
300	12"	323.85	3.96	4.57	9.52
350	14"	355.60	3.96	4.78	
400	16"	406.40	4.19	4.78	
450	18"	457.20	4.19	4.78	
500	20"	508.00	4.78	5.54	
550	22"	558.80	4.78	5.54	
600	24"	609.60	5.54	6.35	
750	30"	762.00	6.35	7.92	
32"		812.8	厚度(Thickness):6.35~30mm 生產規格/厚度買賣雙方協議之 Nominal diameter and wall thickness subject to the approval of vendor and purchaser		
80"		2032.0			

用途：石化、造紙、釀酒、瓦斯、蒸汽、自來水、污水處理、下水道工程...等。
Application: chemical plant, petero-chemical plant, pulp & paper mill, beverage plant, water transport system power plant ect.

地址：435 台中縣梧棲鎮港南路 2 段 562 巷 20 號

網址：<http://www.jinhong.com.tw>

電話：(04)26300188 <公司代表號> 傳真：(04)26305333

電話：(04)26380369 <雷射部專線> 傳真：(04)26303396