



壓力配管用碳鋼鋼管 (Carbon Steel P pipes for Pressure Service)

CNS 4626 G3111 中國國家標準

壓力配管用碳鋼鋼管之尺度及重量

標稱管徑 DESIGNATOR		外徑 O.D.	標稱厚度號數									
			Sch 10		Sch 20		Sch 30		Sch 40		Sch 60	
			厚度 THICK	單位重量 WEIGHT	厚度 THICK	單位重量 WEIGHT	厚度 THICK	單位重量 WEIGHT	厚度 THICK	單位重量 WEIGHT	厚度 THICK	單位重量 WEIGHT
A	B	mm	mm	kg/m	mm	kg/m	mm	kg/m	mm	kg/m	mm	kg/m
15	1/2	21.7	—	—	—	—	—	—	2.8	1.31	3.2	1.46
20	3/4	27.2	—	—	—	—	—	—	2.9	1.74	3.4	2.00
25	1	34.0	—	—	—	—	—	—	3.4	2.57	3.9	2.89
32	1 1/4	42.7	—	—	—	—	—	—	3.6	3.47	4.5	4.24
40	1 1/2	48.6	—	—	—	—	—	—	3.7	4.10	4.5	4.89
50	2	60.5	—	—	3.2	4.52	—	—	3.9	5.44	4.9	6.72
65	2 1/2	76.3	—	—	4.5	7.97	—	—	5.2	9.12	6.0	10.4
80	3	89.1	—	—	4.5	9.39	—	—	5.5	11.3	6.6	13.4
90	3 1/2	101.6	—	—	4.5	10.8	—	—	5.7	13.5	7.0	16.3
100	4	114.3	—	—	4.9	13.2	—	—	6.0	16.0	7.1	18.8
125	5	139.8	—	—	5.1	16.9	—	—	6.6	21.7	8.1	26.3
150	6	165.2	—	—	5.5	21.7	—	—	7.1	27.7	9.3	35.8
200	8	216.3	—	—	6.4	33.1	7.0	36.1	8.2	42.1	10.3	52.3
250	10	267.4	—	—	6.4	41.2	7.8	49.9	9.3	59.2	12.7	79.8
300	12	318.5	—	—	6.4	49.3	8.4	64.2	10.3	78.3	14.3	107
350	14	355.6	6.4	55.1	7.9	67.7	9.5	81.2	11.1	94.3	15.1	127
400	16	406.4	6.4	63.1	7.9	77.6	9.5	93	12.7	123	16.7	160
450	18	457.2	6.4	71.1	7.9	87.5	11.1	122	14.3	156	19.0	205
500	20	508.0	6.4	79.2	9.5	117	12.7	155	15.1	184	20.6	248
550	22	558.8	6.4	87.2	9.5	129	12.7	171	15.9	213	—	—
600	24	609.6	6.4	95.2	9.5	141	14.3	210	—	—	—	—
650	26	660.4	7.9	127	12.7	208	—	—	—	—	—	—

註：1.適用種類：STPG 370/STPG 410。(EQUIVAL TO JIS G3454 STPG 370/STPG410)

2.外徑公稱(TOLERANCE ON O.D.):

25A 以下(OR UNDER)±0.3mm，32A 至 300A(OR OVER)±0.8%，  
350A 以上(OR OVER)±0.5%。

3.厚度公差(TOLERANCE ON THICKNESS):

未滿(UNDER)3mm±0.3mm，3mm 以上(OR OVER)±10%

地址：435 台中縣梧棲鎮港南路 2 段 562 巷 20 號

網址：<http://www.jinhong.com.tw>

電話：(04)26300188 <公司代表號> 傳真：(04)26305333

電話：(04)26380369 <雷射部專線> 傳真：(04)26303396